



## Thermo & Insulating Hoses

Multi-layer hose combinations with individually adapted insulation layers

### Product Details

#### Construction / Material

- Type of construction: special hose
- Design of the helix: metal band, formed as a clamping profile
- Material of the helix: steel strip, VA steel 1.4512
- Design of the external spiral: designed as an additional protective profile
- Design of inner and outer hose: insulation made from asbestos-free insulating materials / made from a standard hose based on the Masterflex product portfolio

#### Properties

#### Operating Temperature

#### Delivery Information

- Delivery, type of production: order-related production / production lengths up to approx. 5 m / nominal widths from DN 38 to DN 900 / insulation thicknesses from 20 mm

#### Application Areas

- Areas of application: Plant & Mechanical Engineering

#### Customizing Options

## Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

## Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

### Individual consultation

We offer consultation by  
phone:  
+49 209 97077-112

Product requests via  
[masterflex.de/en](https://www.masterflex.de/en)

### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

